

Product specification Largo Slim Line II and Largo Tunnel Slim Line II

Name	Largo Slim Line II Largo Tunnel Slim Line II		
Description	Largo: Balanced flue build in fire with large frontal fire view . No visible frame. Wood fire with robust wood logs. Black interior. Largo Tunnel As Largo, but two sided fire view (glass pane on front and back side).		
Purpose	Balanced flue fire		
Type of appliance	Built in fire		
Type of combustion	Closed combustion		
Gas	Natural gas G20 or G25		
Flame picture	Yellow log fire, with glowing effect		
Input rating (H _s)	G25: 11.8kW	G20: 13.0kW	
Max output	8.0kW	9.0kW	
Output range	4,8-8,0kW	5,4-9,0kW	
Gas usage high	1290 l/h	1223 l/h	
Gas usage low	780 l/h	736 l/h	
Flue gas flow rate	gr/sec	gr/sec	
Flue gas temperature	351°C	366°C	
CO ₂ -max	3,7%	3,6%	
Min. draught required	5Pa	5Pa	
Efficiency class	2	2	
Energy label			
CE-ID (PIN)	0063BT3222		
Sizes	Largo: Engine WxHxD = 995x1070...1095x(446.5+D*)mm Larg Tunnel Engine WxHxD = 995x1070...1095x(463+2D*)mm Height excluding wall mounting brackets, flue spigot or back plate Built in frame WxH = 813x671mm Bottom of built in frame: min. 150mm D*=thickness front/back side breast		
Flue spigot	Ø150/100mm, top side		
Removal of combustion products	Natural draught. Powervent® not possible.		
Flueing possibilities with wall terminal	gas	min. vertical	max. horizontal notes
	natural gas	1m	4m
	propane	n.a.	n.a.
Control	Natural convection. Either manual or thermostatic modulating control, by means of temperature sensor on RC control, (adjustable on hand held set). Remote includes clock function with day program (on/off twice a day) and automatic night set back.		
Operation	Radiographic remote control 433MHz, battery operated (sender 1x9V, receiver 4x battery AA)		
Ignition	Electronic ignition on pilot burner		
Gas connection	3/8" female (extra straight connector 3/8" male/Ø15mm with compression nut supplied in carton box)		
Weight	130kg		
Special features	Burner system with three burners ((Vario-burner®). Front and rear burner with two chambers, designed for glowing effect (locally) and yellow wood like flames. Third burner integrated in middle wood log. Including: control hatch, wood logs, remote control, batteries, socket wrench no. 8 (for glass window), adjustable wall mounting brackets + mounting material and a straight connector 3/8" male/Ø15mm with compression nut. Adjustable legs. Easy access to appliance with second generation easy release® glass window (Slim Line II). Build in frame of powder coated galvanized steel to prevent corrosion (plaster work).		

	<p>Control hatch with gas control can be mounted up to about 100cm from the center of the appliance. Appliance contains all 'remote parts' with length of 120cm.</p> <p>Breast ventilation mandatory (>200cm²) Aeration of breast via slots in the appliance.</p>
--	---

Modification overview

Date	Nature of modification
18-03-2008	New
16-04-2008	Weight and gas connection added
11-12-2012	Flueing possibilities with wall terminal added



schornsteinmarkt®

Die ganze Welt des Feuers



Schornsteine

- Schornsteinbausätze
- Schornsteinverlängerungen
- Wanddurchführungen

... und vieles mehr!



Kamine

- Kaminöfen
- Pelletöfen
- Holzherde

... und vieles mehr!



Garten

- Gartenkamine
- Holzbacköfen
- Feuerschalen

... und vieles mehr!



Themenwelten

- Sonderanfertigungen
- Pflege & Reinigung
- Holzbearbeitung

... und vieles mehr!



% Sale

Stark reduziert:
Markenprodukte
im Sale-Bereich

... und vieles mehr!

www.schornsteinmarkt.de



RAUCHZEICHEN

Expertenmagazin für Feuerungstechnik

Im Expertenmagazin berichten wir praxisnah und objektiv über Kamin- und Ofentechnik, Schornsteinbau, Entwicklungen der Branche, Produktneuerungen und geben wertvolle Tipps und Anleitungen zum selber machen.

www.schornsteinmarkt.de/rauchzeichen