



designed to be different

**Product specification Metro 130XT/2 RCH and Metro 130XT/3 RCH**

Name	Metro 130XT/2 RCH Metro 130XT/3 RCH			
Description	Metro 130XT/2 Balanced flue build in gas fire with two sided fire view, no visible frame and shallow build in depth. Two versions : Metro 100XT/2 right and Metro 100XT/2 left (glass at right or left hand side, standing in front of the appliance). Several interiors available. Several log and pebble sets available. Metro 130XT/3 Like Metro 100XT/2, but with three sided fire view			
Purpose	Balanced flue fire			
Type of appliance	Build in fire			
Type of combustion	Closed combustion (C <sub>11</sub> C <sub>31</sub> C <sub>91</sub> )			
Gas	Natural gas G20, G25.3 or G25 and propane G31. Conversion from natural gas to propane, v.v., not possible.			
Flame picture	Yellow fire with either twigs or pebbles			
Input rating (H <sub>s</sub> )	G25.3: 14.0kW	G25: 14.0kW	G20: 14.6kW	G31: 14.0kW
Max output	10.2kW	10.2kW	10.8kW	10.6kW
Output range	4.7 -10.2kW	4.7 - 10.2kW	5.6 - 10.8kW	6.0 - 10.6kW
Gas usage high	1500 l/h	1500 l/h	1390 l/h	517 l/h
Gas usage low	690 l/h	690 l/h	720 l/h	295 l/h
Flue gas flow rate	11,3gr/sec	11,3gr/sec	11,0gr/sec	9,1gr/sec
Flue gas temperature	360°C	360°C	367°C	355°C
CO <sub>2</sub> -max	4,20%	4,20%	4,5%	5,2%
Min. draught required	5Pa	5Pa	5Pa	5Pa
Efficiency class	1	1	1	1
Energy label	B			
CE-ID (PIN)	0063CM3071			
Sizes	Metro 130XT/2: Engine WxHxD = 1404x830 ... 880x481mm Build in frame WxHxD = 1321x398x330mm Metro 130XT/3: Engine WxHxD = 1416x830 ... 880x481mm Build in frame WxHxD = 1380x398x330mm Height excluding wall mounting brackets and flue spigot Bottom side build in frame: min 235mm			
Flue spigot	Ø200/130mm, top side in the middle			
Removal of combustion products	Natural draught. Roof terminal, without bends: - reduce to Ø150/100 after 1 <sup>st</sup> meter vertical Roof terminal with bends: - reduce to Ø150/100 after last bend Powervent® possible.			
Flueing possibilities with wall terminal	gas	min. vertical	max. horizontal	notes
	natural gas	0.8m	5m	
	propane	0.8m	5m	
Removal of heat	Natural convection. Breast ventilation mandatory (>200cm <sup>2</sup> ).			
Control	Honeywell ESYS-02 system. Control options: manual or thermostatic. Clock program (week program) with 6 switch points per day.			
Operation	- Radiographic remote control 866MHz, battery operated (2x battery AA). Two way communication. Reading out of fault codes and fault history. Or: - Wireless via tablet (Android or iOS) + app and WIFI, or - Wired, with house management system			
Ignition	Electronic ignition on main burner. No pilot burner.			
Electrical connection	230VAC with earth connection			
Gas connection	Ø15 fitting with compression nut (adapter supplied in carton box)			
Safety	- Ionisation detection. Separate ionisation electrode not only checks ignition, but also cross lighting of main burner. - Explosion hatches			
Accessories and options	- PowerVent - Protective cover gas control Honeywell (needed for safety reasons when installed on a plateau) - Set of support brackets for a plateau - Extension legs - Communication module (needed for external operation via tablet or domotics)			



**designed to be different**

Weight	Metro 130XT/2 RCH: 160kg Metro 130XT/3 RCH: 160kg
Including	Control hatch, wood logs or pebbles, glowing wool, remote control, batteries, socket wrench no 8 (window glass), adjustable wall mounting brackets + mounting material, connector 3/8" male/Ø15 compression nut, and mains wire + plug (EU and UK) L=150cm



designed to be different

Special features	<ul style="list-style-type: none"><li>- Eco-Wave-technics (programmable flame height as function of the time) for lower gas consumption and more lively flames.</li><li>- Supports for plateau adjustable in height:<ul style="list-style-type: none"><li>- highest position: hole in plateau covered by decorative strip. Hole needs not to be sawed/finished neatly. Plateau thickness &gt; 30mm possible.</li><li>- Plateau goes till the glass and is supported by the adjustable brackets. Plateau thickness <math>\leq</math>30mm. Decorative strip is not used.</li></ul></li><li>- Vario burner with zigzag, to give more depth to flame picture</li><li>- Adjustable legs</li></ul>
------------------	--

**Modification review**

Date	Nature of modification
01-04-2014	New specification



# schornsteinmarkt®

Die ganze Welt des Feuers



## Schornsteine

- Schornsteinbausätze
- Schornsteinverlängerungen
- Wanddurchführungen

... und vieles mehr!



## Kamine

- Kaminöfen
- Pelletöfen
- Holzherde

... und vieles mehr!



## Garten

- Gartenkamine
- Holzbacköfen
- Feuerschalen

... und vieles mehr!



## Themenwelten

- Sonderanfertigungen
- Pflege & Reinigung
- Holzbearbeitung

... und vieles mehr!



## % Sale

Stark reduziert:  
Markenprodukte  
im Sale-Bereich

... und vieles mehr!

[www.schornsteinmarkt.de](http://www.schornsteinmarkt.de)



## RAUCHZEICHEN

Expertenmagazin für Feuerungstechnik

Im Expertenmagazin berichten wir praxisnah und objektiv über Kamin- und Ofentechnik, Schornsteinbau, Entwicklungen der Branche, Produktneuerungen und geben wertvolle Tipps und Anleitungen zum selber machen.

[www.schornsteinmarkt.de/rauchzeichen](http://www.schornsteinmarkt.de/rauchzeichen)