

Productspecification Global 90CF

Name	Global 90CF		
Description	<p>Modular hole in the wall fire with frontal fire view, consisting of an engine and several models of fronts. Black smooth or natural interior. Fire with either twigs or white carrara pebbles. For installation without fascia a build in frame is as accessory available. Fit for installation in a class I chimney.</p> <p>The appliance is supplied with a build in cassette. This is built into the chimney breast. It can be connected from the inside to e.g. a flexible flue liner. When this is done, the appliance can be slid into the cassette. Flame supervision with an atmospheric sensing device (oxypilot).</p>		
Purpose	Fire		
Type of appliance	Build in fire		
Type of combustion	Yellow fire with either twigs or carrara pebbles		
Gas	Natural gas G20, G25 or propane G31		
Flame picture	Yellow fire with either twigs or white Carrara pebbles		
Input rating (H _s)	G25: 6.9kW	G20: 6.9kW	G31: 6.9kW
Max output	4.3kW	4.3kW	4.3kW
Output range	3.1 -4.3kW	2.2 -4.3kW	2.6 -4.3kW
Gas usage high	746 l/h	643 l/h	263 l/h
Gas usage low	366 l/h	326 l/h	160 l/h
Flue gas flow rate	7.9gr/sec	6.9gr/sec	6.6gr/sec
Flue gas temperature	251°C	248°C	274°C
CO ₂ -max	2.95%	3.00%	3.57%
Min. draught required	5Pa	5Pa	5Pa
Efficiency class	2		
Energy label	D		
CE-ID (PIN)	--		
Sizes	<p>HxWxD = 509x968x341mm (Height excluding flue spigot)</p> <p>Front Alpha: HxBxD = 447x982x20mm (389x907 inside)</p> <p>Front Bèta: HxBxD = 567x1252x20mm (389x907 inside)</p> <p>Build in frame HxB = 392x908</p>		
Flue spigot	Ø100mm, top side (protected by debris shield)		
Removal of combustion products	Natural draught.		
Control	<p>Either manual or thermostatic modulating control, by means of temperature sensor on RC control, (adjustable on hand held set).</p> <p>Remote includes clock function with day program (on/off twice a day) and automatic night set back.</p>		
Operation	Radiographic remote control 433MHz, battery operated (sender 1x9V, receiver 4x battery AA)		
Ignition	Electronic ignition on pilot burner		
Gas connection	Flexible SST gas hose Ø12, L=120cm, plus straight connector 3/8" male/Ø12mm with compression nut		
Weight	<p>Engine: 63kg</p> <p>Front Alpha: 5kg</p> <p>Front Bèta: 6kg</p>		
Special features	<p>Zig zag vario burner</p> <p>Including: either twigs or white carrara pebbles, remote control, allen key no. 5 (window glass), mounting material (build in cassette) and batteries.</p> <p>Gas control and remote receiver are mounted underneath the burner. For good accessibility the batteries are mounted in a separate battery holder, which can be slid out.</p> <p>Breast ventilation not mandatory (because of the build in cassette)</p>		

Modification review

Date	Nature o0f modification
09-06-2005	New specification
25-04-2008	Gas connection and weight added



schornsteinmarkt®

Die ganze Welt des Feuers



Schornsteine

- Schornsteinbausätze
- Schornsteinverlängerungen
- Wanddurchführungen

... und vieles mehr!



Kamine

- Kaminöfen
- Pelletöfen
- Holzherde

... und vieles mehr!



Garten

- Gartenkamine
- Holzbacköfen
- Feuerschalen

... und vieles mehr!



Themenwelten

- Sonderanfertigungen
- Pflege & Reinigung
- Holzbearbeitung

... und vieles mehr!



% Sale

Stark reduziert:
Markenprodukte
im Sale-Bereich

... und vieles mehr!

www.schornsteinmarkt.de



RAUCHZEICHEN

Expertenmagazin für Feuerungstechnik

Im Expertenmagazin berichten wir praxisnah und objektiv über Kamin- und Ofentechnik, Schornsteinbau, Entwicklungen der Branche, Produktneuerungen und geben wertvolle Tipps und Anleitungen zum selber machen.

www.schornsteinmarkt.de/rauchzeichen